

BEVMAX

35 SELECT • MODEL 3800-4

4

BEVMAX VALUE IN A SMALLER FOOTPRINT

PRODUCT DISPLAY • CONSUMER CONVENIENCE • RELIABILITY



SAME FOOTPRINT AS A
STANDARD STACK
MACHINE



MEETS ANSI
AND NEW ADA
REQUIREMENTS



EXCEEDS ENERGY
STAR TIER 3 AND
2013 D.O.E.
STANDARDS

CRANE MERCHANDISING SYSTEMS

BEVMAX

35 SELECT • MODEL 3800-4

4

...two times more energy efficient than machines made five years ago -



ENERGY EFFICIENT REFRIGERATION PLATFORM

Tier 3



BevMax4 exceeds ENERGY STAR Tier 3 Standards. The only Glass Front to exceed the Department of Energy 2013 Conservation Standards.

	kWh per year	Increased Operating Costs per Year	
BevMax4 - Narrow	1376		
Competitor A	2042	\$73.46	+48%
Competitor B	2100	\$79.86	+53%
5-Year Old Machine	2871	\$164.90	+109%

Based on the national average cost per kWh in January 2009 of \$0.1103/kWh. Actual energy usage may vary based on environmental conditions.

Only BevMax4 has been designed to enhance the consumer experience and meet the operational needs of bottlers and vending operators.



35
Selections
+ 280
Capacity

in a 39" standard stack footprint



RELIABILITY.

The most reliable, dependable vending solution proven by independent lab tests of 20,000 operating vends; 80,000 vend life-cycles and comprehensive field testing exceeding 238,000 vends.

VERSATILITY.

Increase sales and profitability by replacing an aging 10-12 select stack vender. With a similar footprint to most stack machines, the BevMax4 Narrow offers an alternative size for locations where space is a premium.

EFFICIENCY.

A "shimless" vend mechanism addresses costly labor and service concerns. Load any package in any position. Eliminate loading errors. Load fast with both hands. Bottles remain firmly in place (even if the machine is rocked).

SPEED.

Who likes to wait in line? BevMax4 delivers product in only 8-seconds. Faster delivery time increases sales; speed of service and customer satisfaction.

SIMPLIFIED MAINTENANCE

Low profile modular refrigeration platform removes from the front or the back of the machine.



SPECIFICATIONS

DIMENSIONS

72" H x 39" W x 32" D
(183cm H x 120cm W x 82cm D)

WEIGHT

545 lbs. empty (247 kg)

ELECTRICAL

115 VAC, 60Hz, 10.2 amps
MDB Level 3 Controller

REFRIGERATION

134A CFC-Free Refrigerant Gas
1/3 HP Compressor

CERTIFICATIONS

UL, CUL, CE, FCC, NOM, CTICK

Distributed By :



www.vendohio.com

Area Wide Inc.

4753 E. Lower Springboro Rd.
Waynesville, OH 45068
Phone: 1-800-233-5413
Fax : 1-513-897-7696
e-mail: vending@earthlink.net